

Product Information



3875ZJJ160R05 LEFT

EAN 4031582328578

Walkway caster with automatic side brake for moving walkways, housing made of pressed steel, bright zinc plated, blue passivated, double ball bearing swivel head, flanged wheel with one ball race, left and right hand design, wheel axle with nut, Wheel center made of plastic, Tread: TENTEprene (thermoplastic rubber), with threadguards, roller bearing. Designed for the following pallet size: track width: approx. 2,75 mm, groove width: approx. 5,7 mm, groove depth: > 10 mm. **Hint:** Load capacity 160 kg per caster on level and securely attached floors, 40 kg per caster on walkways. Use on uneven floors, outdoors (ground beams, gaps, joints, manhole covers, etc.) can affect the life expectancy of casters.



Technical Data

Wheel diameter	160 mm
Tread width	40 mm
Bolt-Ø	28 mm
Bolt length	45 mm
Offset	55 mm
Swivel Interference	123 mm
Overall height	190 mm
Temperature	- 20 / + 60 °C
Standard	EN 12532
Weight	2.151 kg
Load capacity (dynamic)	160 kg
Load capacity (static)	320 kg
Hardness of tread	A 87 Shore

Roll performance	+	+	+	+	+
Movement noise	+	+	+	+	+
Attrition	+	+	+	+	+
Corrosion resistance	+	+	+	+	+

Product Information



3875ZJJ160R05 LEFT

EAN 4031582328578

