

# Product Information



## LINEA

### 5947UAP100P30-11 RAL9002

EAN 4031582368673

Swivel caster with total lock, trailing end of caster, housing made of Polyamide, precision ball bearing in swivel head. Wheel center made of Polyamide, Tread: Polyurethane, precision ball bearing, bolt hole

#### Technical Data

|                         |                |
|-------------------------|----------------|
| Wheel diameter          | 100 mm         |
| Tread width             | 20 mm          |
| Caster width            | 82 mm          |
| Center hole             | 11 mm          |
| Dome-Ø                  | 52 mm          |
| Offset                  | 32 mm          |
| Swivel Interference     | 180 mm         |
| Overall height          | 119 mm         |
| Temperature             | - 10 / + 40 °C |
| Standard                | EN 12530       |
| Weight                  | 0.75 kg        |
| Load capacity (dynamic) | 100 kg         |
| Load capacity (static)  | 200 kg         |
| Hardness of tread       | A 92 Shore     |



|                      |   |   |   |   |   |
|----------------------|---|---|---|---|---|
| Roll performance     | + | + | + | + | + |
| Movement noise       | + | + | + | + | + |
| Attrition            | + | + | + | + | + |
| Corrosion resistance | + | + | + | + | + |

# Product Information



## LINEA

**5947UAP100P30-11 RAL9002**

EAN 4031582368673

